

# SMALTOTONE

## ACRYLIC EMULSION – VINYL RESINS

### GENERAL CHARACTERISTICS

High quality mat emulsion paint for walls, gypsum board, plasters and concrete. It has excellent adhesion and elasticity. It can be used to paint new or old painted walls and concrete surfaces. The durability against UV radiation and difficult weather conditions is excellent as on to alkali surfaces. It is easy to apply and presents very good levelling, high performance, whiteness and covering power.

### TECHNICAL CHARACTERISTICS

**Texture:** Mat (EN 13300/<5) with sheen up to 6-10 units at 85°.

**Specific gravity:** 1,46 – 1,49 kg/lit (white).

**Covering power:** 11 – 13 m<sup>2</sup> /lit per layer depending on the surface.

**Dilution:** 8 – 15% on volume with water.

**Drying:** Dry to touch in ½ - 1 hour. The paint adopts full resistance in washing 3–4 weeks after stain.

**Recoatibility:** 4 – 6 hours. This time could elongate under cold and wet weather conditions (humidity).

**Colour shades:** White and thousand shades via Color Moods VECHRO Tinting System.

**PACKING:** Available at 1lt, 4lt & 10lt.

**APPLICATION EQUIPMENT:** Brush, roller and AIRLESS spray.

### SURFACE PREPARATION

Clean the surface of dust, oil, cropped old paints, oxidized surfaces, dampness residues etc, so as to achieve maximum paint adhesion. Prime with SMATDODUR HYDRO.

### APPLICATION - CLEANING EQUIPMENT

Stir well before use. Apply two coats SMALTOTONE.

While working keep your equipment wet, either in the pot or in the paint launder. Strain well your tools from paint back to the pot and clean immediately with water and soap. If paint dries on your tools, it can be removed with high-force detergents only. Avoid washing materials entering into watercourses.

### APPLICATION CONDITIONS

Temperature 8°-30°C and relative humidity lower than 80%. Adverse weather conditions during application may degrade paint's quality.

**STORAGE CONDITIONS**

Close container well after application, so that it is properly kept for future use. Store in a cool place. Protect from freezing and sun exposure.

**LABELLING**

SMALTOTONE needs no danger symbols according to EC legislation.