

## **SMALTOTONE 100% ACRYLIC**

### **FLAT EMULSION 100% ACRYLIC PAINT**

#### **GENERAL CHARACTERISTICS**

High quality 100% acrylic emulsion paint for exterior use. It can be used to paint new or old painted walls and concrete surfaces. It has excellent adhesion and elasticity. The durability against UV radiation and difficult weather conditions is excellent as on to alkali surfaces. It is easy to apply and presents very good levelling, high performance, whiteness and covering power. Excellent long lasting bright colours.

#### **TECHNICAL CHARACTERISTICS**

**Texture:** Mat velvet with sheen up to 8 -12 units at 85°.

**Specific gravity:** 1,44 – 1,46 kg/lt.

**Covering power:** 11 – 13 m<sup>2</sup> /lt per layer depending on the surface.

**Dilution:** 8 – 15% on volume with water.

**Drying:** Dry to touch in ½ - 1 hour. The paint adopts full resistance in washing 3-4 weeks after stain.

**Recoatibility:** ~~4~~ 6-6.3 - 5 hours. This time could elongate under cold and wet weather conditions (humidity).

**Colour shades:** White and thousand shades via Color Moods VECHRO Tinting System.

**PACKING:** Available at ~~1lt, 4lt~~ White: 750ml, 3lt, & 10lt.

**APPLICATION EQUIPMENT:** Brush, roller and AIRLESS spray.

#### **SURFACE PREPARATION**

Clean the surface of dust, oils, cropped paints, dampness etc. Sandpaper well. Surfaces painted with white lime, glue, old paints or, new surfaces shall be painted before with **Smaltodur Silicone or SMALTODUR primer**. Dirty surfaces (nicotine, dump, smoke) are primed with **SMALTOX mono**.

#### **APPLICATION - CLEANING EQUIPMENT**

Stir well before use. Apply two coats SMALTOTONE ACRYLIC.

While working keep your equipment wet, either in the pot or in the paint launder. Strain well your tools from paint back to the pot and clean immediately with water and soap. If paint dries well on your tools, it can be removed only with strong detergents.

#### **APPLICATION CONDITIONS**

Temperature 8°-30°C and relative humidity lower than 80%. New cementinous surfaces could be dried 3 – 4 weeks before priming. Adverse weather conditions during application may degrade paint's quality.

#### **STORAGE CONDITIONS**

Close container well after application, so that it is properly kept for future use. Store in a cool place. Protect from freezing and sun exposure.

**SAFETY INSTRUCTIONS**

- Keep out of the reach of children
- If swallowed, seek medical advice immediately and show this container or label.

**LABELLING**

SMALTOTONE ACRYLIC needs no danger symbols according to EC legislation.