

ULLTRA colorline

100% ACRYLIC

100% acrylic paint

GENERAL CHARACTERISTICS

Acrylic paint, suitable both for internal and external use. It can be used for the painting of new surfaces and walls, plasters and cementitious surfaces, which have been well prepared with the suitable primer. It combines great covering properties, levelling, excellent whiteness and is easy to work with. It is an inexpensive solution for surfaces that are often repainted.

TECHNICAL CHARACTERISTICS

Texture: Flat up to 6-10 units in 85°.

Specific gravity: 1,46 – 1,50 kg/lt.

Covering power: 9-11 m²/lt per layer depending on the surface.

Dilution: 5 – 10% on volume with water.

VOC class: "Exterior wall coatings of mineral substrate". Type Y. VOC limit =40 gr/lt. Max VOC of product ready for use= 20 gr/lt. It meets the requirements of E.C. legislation after 2011. VOC: organic volatile compounds with boiling point < 250°C.

Drying: Touch free after 1-2 hours. The paint adopts full resistance in washing 3-4 weeks after application.

Recoatibility: Recoatable after 4-6 hours from application. This time may prolong under cold and wet weather conditions.

Color shades: White

PACKING: 3lt & 9lt.

APPLICATION EQUIPMENT: Brush, roller, AIRLESS spray.

SURFACE PREPARATION

Clean the surface of dust, oil, cropped paints and dampness. Sandpaper well. Surfaces painted with white lime, glue, old paints or, new surfaces shall be painted before with **Smaltodur Silicone or SMALTODUR primer**. Dirty surfaces (nicotine, dump, smoke) are primed with **SMALTOX**.

APPLICATION

Stir well before use. Apply two coats **ULLTRA colorline 100% Acrylic**.

CLEANING EQUIPMENT

While working keep your equipment wet, either in the pot, or in the paint lauder. Strain well your tools from paint back to the pot and clean immediately with water and soap. If paint dries on your tools, it can be removed only with strong detergents.

APPLICATION CONDITIONS

Temperature 8°-30°C and relative humidity lower than 80%. New cementinous surfaces should dry for a period of 3-4 weeks, before priming. Contrary weather conditions may degrade paint's quality.

STORAGE CONDITIONS

Close well after use. Store in a cool place. Protect from freezing and direct sun exposure.

SAFETY PHRASES

Keep out of the reach of children.

LABELLING

ULLTRA colorline 100% Acrylic needs no hazard symbols according to EC and National legislation.